80-771

DURA-PLEX HI PERFORMANCE CHAIN & CABLE LUBE

[HMIS RATING			NFPA 704 RATING		
ſ	Health	2	MATERIAL	Health	2	
ľ	Flammability	4	SAFETY DATA	Flammability	4	
Ì	Reactivity	0	SHEET	Reactivity	0	
K	IMBALL-MIDWES	т		NFPA 30B LE	VEL	
	O. BOX 2470	2216	470	N/A		
	OLUMBUS, OH 4 ORPORATE TELEF					
E	MERGENCY TELE	PHON	: 800-424-9300			
		1.	PRODUCT IDENTIFICATI	ON		
				-		
Ρ	RODUCT NAME		DURA-PLEX Hi-Perforr Lube	mance Chain & Ca	ble	
	OT SHIPPING		Consumer Commodit			
			HAZARDOUS INGREDIEN			
	PECIFIC CHEMICAL IDEN n-Hexane (110-54-3)	ITITY, CO		ACGIH TLV STEL 50ppm	% <30	
Olefin Polymer (Proprietary)			5mg/m ³ 5	5mg/m ³ 10mg/m ³	3 <30	
Pı	opane/Isobutane/N	-Butane	(68476-86-6) 800ppm 8	300ppm -	<25	
			dwithanasterisk(*)aretoxicchemicalssubje mentsand Reauthorization Act (SARA) of 1			
n	otifyeachpersontowh	omthisr	nixtureoftradenameproductissold.Thissta	tementmustnotbede	tached.Any	
c	opy or redistribution	of this	Material Safety Data Sheet shall include	this statement. **Ce	iling	
			3. PHYSICAL DATA			
			43 - 1	59°F		
			70°FN/A			
			>1	ible		
			: 1) 0.6914			
			TN/A			
			=1)<1			
A	PPEARANCE AND	ODOF	Dark g solven		with	
-		4				
			FIRE AND EXPLOSION D			
			156°F %)9.5			
			(%)			
			Fire-fig	abting foam CO	day	
			chemi	cal, Water fog .		
S	PECIAL FIREFIGHT	FING PI	ROCEDURES Contai			
			if exposed to heat (fire). contained breathing app			
			(MSHA/NIOSH) and full prote	ective cans.		
F	IRE AND EXPLOSI	ON HA	ZARDS			
			of ignition and flash back. product residue (liquid ar			
			dangerous. Do not pres			
			solder, drill, grind, or expos			
			flamer sparks, static electr			
				ignition; they may explode or cause injury or death. Empty drums should be drained, properly bunged		
and promptly returned to a drum recon						
_			promptly disposed of.			
-			5. HEALTH EFFECTS DAT	A		
			HORT TERM EFFECTS OF EXPOSU			
R	OUTE OF ENTRY		Skin Contact, Skin Absorpt and Eye Contact.	tion, Inhalation, I	Ingestion	
	EALTH HAZARDS					
(A	ACUTE AND CHRC	DNIC)	Overexposure may cause ne		age, lung	
E	YE CONTACT			damage and kidney damage. .Irritation causes pain, tearing, reddening and swelling.		
			accompanied by stinging se	nsation.	5	
5	KIN CONTACT		Prolonged or repeated cont	act could cause o	ierattting	

and drying of skin. Irritation to skin and dermatitis. Harmful or fatal if swallowed. Corrosive and may cause.

severe & permanent damage to mouth, throat and

Headaches, dizziness, nausea, decrease blood pressure, changes in heart rate and cyanosis may result from

	FIRST AID PROCEDURES
EYE CONTACT	Hold eyelids apart and immediately flush eyes with plenty of water. Get medical attention, if irritation persists.
SKIN CONTACT	Immediately flush skin with plenty of water. Remove Clothing. Get medical attention immediately. Wash clothing separately before reuse.
INGESTION	Get medical attention immediately. If swallowed, DO NOT INDUCE VOMITING unless directed to do so by medical personnel. Never give anything by mouth to an unconscious victim or a person losing consciousness.
INHALATION	Remove the person away from exposure to fresh air. If not breathing give artificial respiration. If have trouble breathing, give oxygen. Get immediate medical

5. HEALTH EFFECTS DATA CON'T

SPECIAL HEALTH EFFECTS

CARCINOGEN (OSHA Guidelines) Not presently on any lists.

attention

6. REACTIVITY					
STABILITY	. Stable				
INCOMPATIBILITIES	Strong acids, alkalis, oxidizers and amines. All sources of ignition, welding arcs and open flames.				
HAZARDOUS DECOMPOSITION					
PRODUCTS	Oxides of carbon, nitrogen and may produce forms of chloride, chlorine and phosgene.				
HAZARDOUS POLYMERIZATION	.Will not occur under normal conditions.				
HAZARDOUS POLYMERIZATION CONDITIONS	. None known.				

7. PRECAUTIONS FOR SAFE HANDLING & USE

PROTECTIVE EQUIPMENT	
REQUIREMENTS	Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during use. NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge. Where contact is expected wear chemical resistant gloves, a chemical suit, rubber boot, and chemical safety goggles and plus face shield.
WASH REQUIREMENTS	Wash with soap and water.
SPILL OR LEAK PROCEDURES	Absorb spill with inert material (e.g. dry sand or earth), then place in chemical waste container.
WASTE DISPOSAL METHODS	Dispose of in accordance with local, state, and federal regulations.
HANDLING & STORAGE	Wash thoroughly after handling. Do not allow to freeze. Avoid temperatures above 120°F
OTHER PRECAUTIONS	"Use NIOSH approved respirator with an organic vapor cartridge; avoid prolonged breathing of vapors; protection provided by air purifying respirators is limited.

8. ADDITIONAL INFORMATION

Use self-contained breathing apparatus if TLV limits are exceeded. Do not eat or smoke while using. Wash hands after use. Use positive pressure air supplied respirator if there is potential for uncontrolled release, if exposure levels are unknown, or in any circumstance where air purifying respirators may not provide adequate protection.

THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT(S) ALONE AND ARE NOT COMBINED WITH OTHER PRODUCTS. SUCH INFORMATION IS BASED UPON OUR RESEARCH AND ON DATA FROM OTHER RELIABLE SOURCES AND IS BELIEVED TO BE ACCURATE. NO GUARANTEE OF ACCURACY IS MADE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFY THIS DATA UNDER THEIR OWN OPERATING CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.



Specializing in Materials Management since 1923

stomach.

overexposure.

INGESTION.

INHALATION ..