

Printing date 02/06/2015

Reviewed on 02/06/2015

1 Identification

- Product identifier
- Trade name: SOLV-ALL 2 METAL PARTS SOLVENT
- · Article number: 80-929
- · Application of the substance / the mixture Coolant/ Cutting solution

· Recommended use and restriction on use

- · Recommended use: Coolant/cutting solution
- · Restrictions on use: No further relevant information available.

· Details of the supplier of the Safety Data Sheet · Manufacturer/Supplier: Kimball-Midwest IÌ €€ÂIJ[à^!œÂIJ[æå Columbus, OH 432QÌ Phone: (Ì €€) 2HH-FGJI

• Emergency telephone number: CHEMTREC 1-800-424-9300 (US/Canada) Á

2 Hazard(s) identification

· Classification of the substance or mixture

GHS04 Gas cylinder

Press. Gas H280 Contains gas under pressure; may explode if heated.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • Hazard pictograms



· Signal word Warning

Hazard-determining components of labeling: tetrachloroethylene dichloromethane Hazard statements H280 Contains gas under pressure; may explode if heated.

H351 Suspected of causing cancer.

(Contd. on page 2)



3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerou	us components:		
127-18-4	tetrachloroethylene	🚸 Carc. 2, H351	60-80%
75-09-2	dichloromethane	🚸 Carc. 2, H351	10-20%
67-64-1	acetone	 Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336 	1-5%
124-38-9	carbon dioxide	🔶 Press. Gas, H280	1-5%
		(Contd	. on page 3)

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/06/2015

Reviewed on 02/06/2015

Trade name: SOLV-ALL 2 METAL PARTS SOLVENT

· Additional information:

For the listed ingredients, the identity and exact percentages are being withheld as a trade secret.

4 First-aid measures

· Description of first aid measures

· General information: Take affected persons out into the fresh air.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Unlikely route of exposure.

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

· Information for doctor:

Most important symptoms and effects, both acute and delayed

Headache Coughing Nausea Gastric or intestinal disorders when ingested. Allergic reactions Dizziness Slight irritant effect on skin and mucous membranes.

Irritant to eyes.

- · Danger Suspected of causing cancer.
- Indication of any immediate medical attention and special treatment needed

If necessary oxygen respiration treatment.

Treat skin and mucous membrane with antihistamine and corticoid preparations.

5 Fire-fighting measures

Extinguishing media
Suitable extinguishing agents: Water fog / haze Foam Fire-extinguishing powder Carbon dioxide Sand
For safety reasons unsuitable extinguishing agents: Water stream.
Special hazards arising from the substance or mixture Danger of receptacles bursting because of high vapor pressure if heated. During heating or in case of fire poisonous gases are produced.
Advice for firefighters
Protective equipment: Wear self-contained respiratory protective device.

Wear fully protective suit.

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/06/2015

Reviewed on 02/06/2015

Trade name: SOLV-ALL 2 METAL PARTS SOLVENT

· Additional information

In case of fire involving large quantities, evacuate area and fight fire from the upwind side. Cool endangered receptacles with water fog.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures Use respiratory protective device against the effects of fumes/dust/aerosol. Wear protective equipment. Keep unprotected persons away. Ensure adequate ventilation. Keep away from ignition sources. Protect from heat. · Environmental precautions: Do not allow to enter sewers/ surface or ground water. Inform respective authorities in case of seepage into water course or sewage system. Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents Pick up manually. Send for recovery or disposal in suitable receptacles. Dispose contaminated material as waste according to item 13. **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling: · Precautions for safe handling Use only in well ventilated areas. Avoid splashes or sprav in enclosed areas. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. Information about protection against explosions and fires: Pressurized container: protect from sunlight and do not expose to temperatures exceeding 120 °F / 49 °C. i.e. electric lights. Do not pierce or burn, even after use. Keep respiratory protective device available. Pressurised container: May burst if heated. During heating or in case of fire poisonous gases are produced. Conditions for safe storage, including any incompatibilities · Storage: · Requirements to be met by storerooms and receptacles: Store in a cool location. Observe official regulations on storing packagings with pressurized containers. Avoid storage near extreme heat, ignition sources or open flame. (Contd. on page 5)

Printing date 02/06/2015

Reviewed on 02/06/2015

Trade name: SOLV-ALL 2 METAL PARTS SOLVENT

(Contd. of page 4)

 Information about storage in one common storage facility: Store away from foodstuffs. Store away from oxidizing agents.
 Further information about storage conditions: Protect from heat and direct sunlight. Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.
 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

• Components with limit values that require monitoring at the workplace:

127-18-4 tetrachloroethylene		
PEL (USA) Long-term value: 100 ppm Ceiling limit value: 200; 300* ppm *5-min peak in any 3 hrs		
REL (USA)	Minimize workplace exp. concs.;Pocket Guide App. A	
TLV (USA)	TLV (USA) Short-term value: 685 mg/m ³ , 100 ppm Long-term value: 170 mg/m ³ , 25 ppm BEI	
EL (Canada) Short-term value: 100 ppm Long-term value: 25 ppm IARC 2A		
EV (Canada)	Short-term value: 100 ppm Long-term value: 25 ppm	
LMPE (Mexico) Short-term value: 100 ppm Long-term value: 25 ppm A3, IBE		
75-09-2 dichloromethane		
PEL (USA)	Short-term value: 125 ppm Long-term value: 25 ppm see 29 CFR 1910.1052	
REL (USA)	See Pocket Guide App. A	
TLV (USA)	Long-term value: 174 mg/m³, 50 ppm BEI	
EL (Canada) Long-term value: 25 ppm IARC 2B		
EV (Canada)Long-term value: 175 mg/m³, 50 ppmLMPE (Mexico)Long-term value: 50 ppmA3, IBE		
		67-64-1 aceton
PEL (USA)	Long-term value: 2400 mg/m³, 1000 ppm	
	(Contd. on page 6)	

Printing date 02/06/2015

Reviewed on 02/06/2015

Trade name: SOLV-ALL 2 METAL PARTS SOLVENT

		(Contd. of page 5)
REL (USA)	Long-term value: 590 mg/m ³ , 250 ppm	
TLV (USA)	Short-term value: (1782) NIC-1187 mg/m³, (750) NIC-500 ppm Long-term value: (1188) NIC-594 mg/m³, (500) NIC-250 ppm BEI	
EL (Canada)	Short-term value: 500 ppm Long-term value: 250 ppm	
EV (Canada)	Short-term value: 750 ppm Long-term value: 500 ppm	
LMPE (Mexic	o) Short-term value: 750 ppm Long-term value: 500 ppm A4, IBE	
124-38-9 carl	oon dioxide	
PEL (USA)	Long-term value: 9000 mg/m³, 5000 ppm	
REL (USA)	Short-term value: 54.000 mg/m³, 30.000 ppm Long-term value: 9000 mg/m³, 5000 ppm	
TLV (USA)	Short-term value: 54.000 mg/m³, 30.000 ppm Long-term value: 9000 mg/m³, 5000 ppm	
EL (Canada)	Short-term value: 15000 ppm Long-term value: 5000 ppm	
EV (Canada)	Short-term value: 54.000 mg/m³, 30.000 ppm Long-term value: 9.000 mg/m³, 5.000 ppm	
LMPE (Mexic	o) Short-term value: 30000 ppm Long-term value: 5000 ppm	
· Ingredients v	vith biological limit values:	
127-18-4 tetr	achloroethylene	
Ti Pi	edium: end-exhaled air me: prior to shift arameter: Tetrachloroethylene	
M	5 mg/L edium: blood me: prior to shift arameter: Tetrachloroethylene	
75-09-2 dich	oromethane	
	3 mg/L edium: urine me: end of shift arameter: Dichloromethane (semi-quantitative)	
67-64-1 acete		
BEI (USA) 50 M Ti Pa) mg/L edium: urine me: end of shift arameter: Acetone (nonspecific)	
· Additional in	formation: The lists that were valid during the creation were used as basis.	(Contd. on page 7)

Printing date 02/06/2015	Reviewed on 02/06/2015
Trade name: SOLV-ALL 2 METAL PARTS SOLVENT	
	(Contd. of page 6
· Exposure controls	
Personal protective equipment:	
General protective and hygienic measures:	
The usual precautionary measures for handling chemicals Keep away from foodstuffs, beverages and feed.	should be followed.
Immediately remove all soiled and contaminated clothing.	
Wash hands before breaks and at the end of work.	
Use only in well ventilated areas.	
Avoid contact with the eyes and skin.	
Avoid breathing mist, vapors, or spray. Engineering controls: No further relevant information ava	ilabla
· Breathing equipment:	
Use suitable respiratory protective device in case of insuffic	cient ventilation.
For spills, respiratory protection may be advisable.	
NIOSH or EN approved organic vapor respirator equipped	with a dust/mist prefilter should be used.
· Protection of hands:	
Protective gloves	
The glove material has to be impermeable and resistant to	
Selection of the glove material on consideration of the degradation	penetration times, rates of diffusion and the
· Material of gloves	
The selection of the suitable gloves does not only dependent	d on the material, but also on further marks o
quality and varies from manufacturer to manufacturer	
substances, the resistance of the glove material can not be	e calculated in advance and has therefore to be
checked prior to the application.	
 Penetration time of glove material The exact break through time has to be found out by the m 	anufacturer of the protective gloves and has t
be observed.	initial detailer of the proteotive gioves and has t
· Eye protection:	
Safety glasses	
 Body protection: Protective work clothing 	
Limitation and supervision of exposure into the enviro	nment
Avoid release to the environment.	
No further relevant information available.	
9 Physical and chemical properties	
or hysical and chemical properties	
 Information on basic physical and chemical properties 	
· General Information	
· Appearance:	

Appearance: Form:

Color:

Aerosol Colorless

(Contd. on page 8)

Printing date 02/06/2015

Reviewed on 02/06/2015

Trade name: SOLV-ALL 2 METAL PARTS SOLVENT

		(Contd. of page 7)
· Odor:	Solvent-like	(
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
 Change in condition Melting point/Melting range: Boiling point/Boiling range: 	Not applicable, as aerosol. 87 °C (189 °F) (estimated)	
· Flash point:	Not applicable, as aerosol.	
· Flammability (solid, gaseous):	Not applicable.	
• Auto-ignition temperature:	Not determined.	
· Decomposition temperature:	Not determined.	
· Auto igniting:	Product is not self-igniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
 Explosion limits: Lower: Upper: 	Not determined. Not determined.	
· Vapor pressure:	77 hPa (58 mm Hg) (estimated)	
 Density: Relative density Vapour density Evaporation rate 	1.5322 g/mL Not determined. Not determined. Not applicable.	
 Solubility in / Miscibility with Water: 	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water):	Not determined.	
 Viscosity: Dynamic: Kinematic: Other information 	Not determined. Not determined. No further relevant information available.	

10 Stability and reactivity

· Reactivity	
· Chemical stability	
 Thermal decomposition / conditions to be avoided: 	
Danger of receptacles bursting because of high vapor pressure if heated.	
Possibility of hazardous reactions	
Reacts with oxidizing agents.	
Toxic fumes may be released if heated above the decomposition point.	
· Conditions to avoid	
Excessive heat.	
Store away from oxidizing agents.	
	(Contd. on page 9)

Printing date 02/06/2015

Г

Reviewed on 02/06/2015

Trade name: SOLV-ALL 2 METAL PARTS SOLVENT

(Contd. of page 8)

• Incompatible materials: Caution! Do not use in conjunction with other products. Dangerous gases (chlorine) may be given off. • Hazardous decomposition products:

Carbon monoxide and carbon dioxide Chlorine Chlorine compounds

Information on toxicological effects Acute toxicity:	
LD/LC50 values that are relevant for classification:	
127-18-4 tetrachloroethylene	
Oral LD50 2629 mg/kg (rat)	
79-01-6 trichloroethylene	
Oral LD50 2402 mg/kg (mouse)	
Dermal LD50 8450 mg/kg (mouse)	
67-64-1 acetone	
Oral LD50 5800 mg/kg (rat)	
Dermal LD50 20000 mg/kg (rabbit)	
on the skin: Irritant to skin and mucous membranes. on the eye: Irritating effect. Additional toxicological information: Irritant Danger through skin absorption. Inhalation of concentrated vapors as well as oral intake will lead to anaesthesia-lik headache, dizziness, etc. Carcinogenic. Suspected of causing genetic defects. Toxic and/or corrosive effects may be delayed up to 24 hours. Carcinogenic categories NTP (National Toxicology Program) 127-18-4 [tetrachloroethylene]	e conditions a
	F
75-09-2 dichloromethane	
75-09-2 dichloromethane	
75-09-2 dichloromethane OSHA-Ca (Occupational Safety & Health Administration)	

(Contd. of page 9)

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/06/2015

Reviewed on 02/06/2015

Trade name: SOLV-ALL 2 METAL PARTS SOLVENT

· Repeated Dose Toxicity:

May cause damage to organs through prolonged or repeated exposure. Repeated exposures may result in skin and/or respiratory sensitivity.

12 Ecological information

· Toxicity

Aquatic toxicity:

The material is harmful to the environment.

- Toxic for aquatic organisms
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

· Results of PBT and vPvB assessment

- · PBT: Not applicable.
- · **vPvB:** Not applicable.

· Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Contact waste processors for recycling information.

After prior treatment product has to be disposed of in an incinerator for hazardous waste adhering to the regulations pertaining to the disposal of particularly hazardous waste.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14 Transport information

· UN-Number

· DOT, ADR, IMDG, IATA

UN1950

(Contd. on page 11)

Reviewed on 02/06/2015

Safety Data Sheet acc. to OSHA HCS (29 CFR 1910.1200)

Printing date 02/06/2015

Trade name: SOLV-ALL 2 METAL PARTS SOLVENT (Contd. of page 10) · UN proper shipping name Limited Quantity for packages less than 30 kg (66 lb) and inner packagings less than 1 L (0.3 gal). · DOT Aerosols, non flammable 1950 AEROSOLS, CONTAINING SUBSTANCES IN CLASS · ADR 6.1, PACKING GROUP III, ENVIRONMENTALLY HAZARDOUS · IMDG AEROSOLS, AEROSOLS, NON-FLAMMABLE, CONTAINING SUBSTANCES IN CLASS 6.1, PACKING GROUP III (TETRACHLOROETHYLENE), MARINE POLLUTANT ·IATA AEROSOLS, NON-FLAMMABLE, CONTAINING SUBSTANCES IN CLASS 6.1, PACKING GROUP III · Transport hazard class(es) · DOT · Class 2.2 · Label 2.2+6.1 _____ · ADR 2 5T Gases · Class · Label 2.2+6.1 _____ · IMDG · Class 2.2 · Label 2.2+6.1 ·IATA · Class 2.2 · Label 2.2+6.1 · Packing group · DOT, ADR, IMDG, IATA Not Regulated (Contd. on page 12)

Printing date 02/06/2015

Reviewed on 02/06/2015

Trade name: SOLV-ALL 2 METAL PARTS SOLVENT		
	(Contd. of page 11)	
· Environmental hazards:	Product contains environmentally hazardous substances: tetrachloroethylene	
[·] Marine pollutant:	Yes Symbol (fish and tree)	
 Special marking (ADR): 	Symbol (fish and tree)	
· Special precautions for user	Warning: Gases	
Danger code (Kemler):	-	
· EMS Number:	F-D,S-U	
 Segregation groups 	Liquid halogenated hydrocarbons	
Transport in bulk according to Annex II o	f	
MARPOL73/78 and the IBC Code	Not applicable.	
· Transport/Additional information:		
· ADR		
 Excepted quantities (EQ) 	Code: E0	
	Not permitted as Excepted Quantity	
· IMDG		
 Limited quantities (LQ) 	1L	
Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
· UN "Model Regulation":	UN1950, Aerosols, ENVIRONMENTALLY HAZARDOUS,	
	2.2	

15 Regulatory information

 $^{\cdot}$ Safety, health and environmental regulations/legislation specific for the substance or mixture $^{\cdot}$ SARA

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

127-18-4 tetrachloroethylene

79-01-6 trichloroethylene

• TSCA (Toxic Substances Control Act):

All ingredients are listed.

Proposition 65 (California)

· Chemicals known to cause cancer:

127-18-4 tetrachloroethylene

79-01-6 trichloroethylene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

79-01-6 trichloroethylene

(Contd. on page 13)

Printing date 02/06/2015

Reviewed on 02/06/2015

Trade name: SOLV-ALL 2 METAL PARTS SOLVENT

	(Contd. of page
· Chemicals known to cause developmental toxicity:	
79-01-6 trichloroethylene	
Carcinogenic categories	
· EPA (Environmental Protection Agency)	
127-18-4 tetrachloroethylene	L
79-01-6 trichloroethylene	Cal
· IARC (International Agency for Research on Cancer)	
127-18-4 tetrachloroethylene	2/
79-01-6 trichloroethylene	24
· TLV (Threshold Limit Value established by ACGIH)	
127-18-4 tetrachloroethylene	A
79-01-6 trichloroethylene	A
NIOSH-Ca (National Institute for Occupational Safety an	d Health)
127-18-4 tetrachloroethylene	
79-01-6 trichloroethylene	
State Right to Know Listings	
None of the ingredients is listed.	
· Canadian substance listings:	
· Canadian Domestic Substances List (DSL)	
All ingredients are listed.	
· Canadian Ingredient Disclosure list (limit 0.1%)	
None of the ingredients is listed.	
· Canadian Ingredient Disclosure list (limit 1%)	
All ingredients are listed.	

and the SDS contains all the information required by the Controlled Products Regulations. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision 02/06/2015 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 14)

Printing date 02/06/2015

Reviewed on 02/06/2015

Trade name: SOLV-ALL 2 METAL PARTS SOLVENT

(Contd. of page 13)

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) WHMIS: Workplace Hazardous Materials Information System (Canada) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Press. Gas: Gases under pressure: Compressed gas Press. Gas: Gases under pressure: Liquefied gas Flam. Liq. 2: Flammable liquids, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A Carc. 2: Carcinogenicity, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Sources SDS Prepared by: ChemTel Inc. 1305 North Florida Avenue Tampa, Florida USA 33602-2902 Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com