

CUSTOMER: 327598
BATCH #: 2020004
PICK ZONE: RW01
PRODUCT NAME: FREE AEROSOL

ORDER #: 3590758
DELIVERY ID: 15269222
PICK SEQUENCE #: 550
BARCODE #: 12061187

Safety Data Sheet FREE AEROSOL

Supersedes Date 10/17/2013

Issuing Date 03/04/2016

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name FREE AEROSOL
Recommended use Lubricant
Information on Manufacturer
CERTIFIED LABS, DIV. OF NCH CORP.
BOX 152170
IRVING, TEXAS 75015

Product Code 12061187
Chemical nature Solvent blend
Emergency Telephone Number
CHEMTREC® 800-424-9300
Telephone inquiry
972-579-2477

2. HAZARD IDENTIFICATION

Color Amber

Physical state Liquid

Odor Solvent

GHS

Classification

Physical Hazards

Flammable Aerosols
Gases under pressure

Category 1
Compressed Gas

Health Hazard

Aspiration Toxicity
Serious Eye Damage/Eye Irritation
Specific target organ systemic toxicity (single exposure)
Specific target organ toxicity (repeated exposure)

Category 1
Category 2B
Category 3
Category 2


Other hazards

None

Labeling

Signal Word

DANGER



Hazard statements

H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H336 - May cause drowsiness or dizziness
H320 - Causes eye irritation
H304 - May be fatal if swallowed and enters airways
H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary Statements

P210 - Keep away from heat, sparks, open flames or hot surfaces.
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P271 - Use in a well-ventilated area.
P260 - Do not breathe vapor, mist or gas
P264 - Wash face, hands and any exposed skin thoroughly after handling
P270 - Do not eat, drink or smoke when using this product.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312 - Call a physician if unwell.
P337 + P313 - If eye irritation persists, get medical attention.
P304 + P340 - IF INHALED: Remove person to fresh air and keep at rest in a position comfortable for breathing.
P301 + P330 + P331 - IF SWALLOWED: Rinse mouth. DO NOT induce vomiting. Call a physician if unwell.
P233 - Keep container tightly closed
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P403 - Store in a well-ventilated place
P501 - Dispose of contents and container in accordance with applicable local regulations.

20 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS No.	Weight % *
Petroleum distillates, hydrotreated light	64742-47-8	37.96722
Petroleum distillates, hydrotreated light naphthenic (<3% DMSO extractable)	64742-53-6	19.79802
Ethyl acetate	141-78-6	13.5
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	8.7201
Sodium sulfonate	68608-26-4	5.58
Isobutane	75-28-5	5.449
Propane	74-98-6	4.551
Petroleum distillates, solvent dewaxed heavy paraffinic (<3% DMSO extractable)	64742-65-0	2.97
Nonane	111-84-2	0.9179
Water, distilled, conductivity or of similar purity	7732-18-5	0.45
Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S]dioxodi- mu.-thioxodi-, (Mo-Mo)	72030-25-2	0.07425
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	64742-52-5	0.02475

*The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST AID MEASURES

General advice	Avoid breathing vapors, mist, or gas. Avoid contact with skin, eyes and clothing.
Eye Contact	Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get medical attention immediately.
Skin Contact	Wash off with soap and plenty of water. Get medical attention if irritation develops and persists.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention immediately. Never give anything by mouth to an unconscious person.
Notes to physician	Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways.

5. FIRE-FIGHTING MEASURES

Flash Point > 81 °F / > 27 °C	Method Set a closed cup	
Flammability Limits in Air %: Solvent mixture.	Upper: 11.5	Lower: 1.9
Suitable Extinguishing Media		
Water spray. Carbon dioxide (CO ₂). Foam. Dry chemical. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.		
Specific hazards arising from the chemical		
Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: >24 inches / >61 cm and Burnback: 3 inch / 7.5 cm. Material can create slippery conditions.		
Protective Equipment and Precautions for Firefighters		
As in any fire, wear self-contained breathing apparatus pressure -demand, NOHSC (approved or equivalent) and full protective gear.		
Aerosol Level (NFPA 30B) -	3	
NFPA	Health 2	Flammability 4
HMIS	Health 2	Flammability 4
		Instability 0
		Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions	Use personal protective equipment. Remove all sources of ignition. Ensure adequate ventilation. Prevent further leakage or spillage if safe to do so. Material can create slippery conditions.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment	Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Methods for Cleaning Up	Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers.
Neutralizing Agent	Not applicable.

7. HANDLING AND STORAGE

11. TOXICOLOGICAL INFORMATION

Product Information No information available.

The following values are calculated based on chapter 3.1 of the GHS document

Dermal LD50 No information available

Inhalation LC50

Gas No information available

Mist No information available

Vapor No information available

Principle Route of Exposure Inhalation, Skin contact, Eye contact.

Primary Routes of Entry Skin contact, Skin Absorption.

Acute Effects:

Eyes Causes eye irritation.

Skin Repeated exposure may cause skin dryness or cracking.

Inhalation May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May cause central nervous system depression. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Ingestion Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration hazard if swallowed - can enter lungs and cause damage. May be fatal if swallowed and enters airways.

Chronic Toxicity

Target Organ Effects

Aggravated Medical Conditions

Component Information

Acute Toxicity

Repeated and prolonged exposure to solvents may cause brain and nervous system damage.

Central nervous system, Respiratory system, Skin, Eyes.

Respiratory system, Skin disorders, Neurological disorders.

Component	Oral LD50	Dermal LD50	Inhalation LC50	Draize Test	Other
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	no data available	no data available	no data available
Ethyl acetate 141-78-6	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit)	no data available	no data available	no data available
Solvent naphtha (petroleum), medium aliphatic 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h	no data available	no data available
Isobutane 75-28-5	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available
Propane 74-98-6	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available
Petroleum distillates, solvent dewaxed heavy paraffinic (<3% DMSO extractable) 64742-65-0	>5000 mg/kg (rat)	>5000 mg/kg (rabbit)	no data available	no data available	no data available
Nonane 111-84-2	no data available	no data available	= 3200 ppm (Rat) 4 h	no data available	no data available
Water, distilled, conductivity or of similar purity 7732-18-5	> 90 mL/kg (Rat)	no data available	no data available	no data available	no data available
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable) 64742-52-5	> 5000 mg/kg (Rat)	> 5000 mg/kg (Rabbit)	no data available	no data available	no data available

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Ethyl acetate 141-78-6	no data available	no data available	no data available	no data available	Skin Eyes Respiratory system
Isobutane 75-28-5	no data available	no data available	no data available	no data available	Central nervous system
Propane 74-98-6	no data available	no data available	no data available	no data available	Central nervous system
Nonane 111-84-2	no data available	no data available	no data available	no data available	Skin Central nervous system Eyes Respiratory system
Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-S,S]dioxodi-mu-thioxi-di-, (Mo-Mo) 72030-25-2	no data available	no data available	no data available	no data available	Blood Eyes Respiratory system Kidney

Carcinogenicity

There are no known carcinogenic chemicals in this product.

Handling	Keep away from heat and sources of ignition. Avoid breathing vapors, mist or gas. Avoid contact with skin, eyes and clothing.			
Storage	Keep away from open flames, hot surfaces and sources of ignition. Store in original container. Keep containers tightly closed in a dry, cool and well-ventilated place.			
Storage Temperature	Minimum	35 °F / 2 °C	Maximum	120 °F / 49 °C
Storage Conditions	Indoor	X	Outdoor	
			Heated	Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Petroleum distillates, hydrotreated light	525 mg/m ³ TWA	No data available	No data available
Petroleum distillates, hydrotreated light naphthenic (<3% DMSO extractable)	5 mg/m ³ as oil mist	10 mg/m ³ as oil mist	No data available
Ethyl acetate	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³	2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³
Isobutane	STEL: 1000 ppm	No data available	TWA: 800 ppm TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
Petroleum distillates, solvent dewaxed heavy paraffinic (<3% DMSO extractable)	TWA: 5 mg/m ³ STEL: 10 mg/m ³	TWA: 5 mg/m ³	No data available
Nonane	TWA: 200 ppm	No data available	TWA: 200 ppm TWA: 1050 mg/m ³
Molybdenum, bis(O,O-bis(2-ethylhexyl)phosphorodithioato-S,S)dioxodi-mu.-thioxodi-, (Mo-Mo)	TWA: 0.5 mg/m ³	TWA: 5 mg/m ³	No data available
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	TWA: 5 mg/m ³ ; STEL: 10 mg/m ³	TWA: 5 mg/m ³	No data available

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

Eye/Face Protection

Safety glasses with side-shields.

Skin Protection

Wear suitable protective clothing, Impervious gloves.

Respiratory Protection

In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations

Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Liquid	Viscosity	Non viscous
Color	Amber	Odor	Solvent
Odor Threshold	Not applicable	Appearance	Transparent - Hazy
pH	Not applicable	Specific Gravity	0.797
Evaporation Rate	19.12 (Butyl acetate=1)	Percent Volatile (Volume)	75.2
VOC Content (%)	41.90	VOC Content (g/L)	333.9
Vapor Pressure	1546.78 mmHg @ 70 °F	Vapor Density	1.4
Solubility	Negligible	n-Octanol/Water Partition	No data available
Melting Point/Range	No data available	Decomposition Temperature	No data available
Boiling Point/Range	> 160 °F / 71 °C	Flammability (solid, gas)	No data available
Flash Point	> 81 °F / > 27 °C	Method	Seta closed cup
Autoignition Temperature	No information available.		
Flammability Limits in Air %:	Solvent mixture	Upper: 11.5 Lower: 1.9	

10. STABILITY AND REACTIVITY

Chemical Stability

Stable. Hazardous polymerization does not occur.

Conditions to Avoid

Keep away from open flames, hot surfaces, and sources of ignition.

Incompatible Products

Strong oxidizing agents, Reducing agents, Strong acids, Strong bases, Amines, Nitric acid.

Decomposition Temperature

No data available

Hazardous Decomposition Products

Carbon oxides, Nitrogen oxides (NOx), Sulfur oxides, Aldehydes, Ketones, Hydrocarbons.

Possibility of Hazardous Reactions

None under normal processing.

12. ECOLOGICAL INFORMATION

Product Information No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Crustacea	log Pow
Petroleum distillates, hydrotreated light	No information available.	LC50 = 45 mg/L Pimephales promelas 96 h LC50 = 2.2 mg/L Lepomis macrochirus 96 h LC50 = 2.4 mg/L Oncorhynchus mykiss 96 h	No information available	No information available.	N/A
Petroleum distillates, hydrotreated light naphthenic (<3% DMSO extractable)	No information available.	LC50 > 5000 mg/L Oncorhynchus mykiss 96 h	No information available	1000: 48 h Daphnia magna mg/L EC50	N/A
Ethyl acetate	No information available.	LC50 220 - 250 mg/L Pimephales promelas 96 h LC50 = 484 mg/L Oncorhynchus mykiss 96 h LC50 352 - 500 mg/L Oncorhynchus mykiss 96 h	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	560: 48 h Daphnia magna mg/L EC50 Static	0.6
Solvent naphtha (petroleum), medium aliphatic	EC50 = 450 mg/L Pseudokirchneriella subcapitata 96 h	LC50 = 800 mg/L Pimephales promelas 96 h	No information available	100: 48 h Daphnia magna mg/L EC50	N/A
Isobutane	No information available.	No information available.	No information available	No information available.	2.88
Propane	No information available.	No information available.	No information available	No information available.	2.3
Petroleum distillates, solvent dewaxed heavy paraffinic (<3% DMSO extractable)	No information available.	LC50 > 5000 mg/L Oncorhynchus mykiss 96 h	No information available	1000: 48 h Daphnia magna mg/L EC50	N/A
Petroleum distillates, hydrotreated heavy naphthenic (<3% DMSO extractable)	No information available.	LC50 > 5000 mg/L Oncorhynchus mykiss 96 h	No information available	1000: 48 h Daphnia magna mg/L EC50	N/A

Persistence and Degradability No information available.

Bioaccumulation No information available.

Mobility No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal Dispose of in accordance with local regulations.
Container Disposal Contents under pressure. Do not puncture. Empty remaining contents. Empty containers should be taken for local recycling, recovery, or waste disposal.

14. TRANSPORT INFORMATION

DOT

Proper Shipping Name Consumer Commodity
Hazard Class ORM-D
Description Consumer Commodity, ORM-D

TDG

Proper shipping name Consumer Commodity
Hazard Class ORM-D
UN-No UN1950
Description Consumer Commodity, ORM-D

ICAO

UN-No UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1
Shipping Description UN1950, Aerosols, flammable, 2.1, LTD QTY

IATA

UN-No UN1950
Proper Shipping Name Aerosols, flammable
Hazard Class 2.1
ERG-Code 126
Shipping Description UN1950, Aerosols, flammable, 2.1, LTD QTY

IMDG/IMO

Proper Shipping Name Aerosols, flammable

Hazard Class 2.1
 UN-No UN1950
 EmS No. F-A, S-A
 Description UN1950, Aerosols, flammable, 2.1, LTD QTY

15. REGULATORY INFORMATION

Inventories
 TSCA Complies
 DSL Complies
 U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	Yes	Yes	Yes	No

CERCLA

Component	Hazardous Substances RQs	CERCLA EHS RQs
Ethyl acetate	5000 lb	Not applicable

16. OTHER INFORMATION

Prepared By Adrienne McKee
 Supersedes Date 10/17/2013
 Issuing Date 03/04/2016
 Reason for Revision No information available.
 Glossary No information available.
 List of References. No information available.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.